

Counter Chiller & Freezer

平台冷柜

Key Features

- 1. Patented semi frequency variable technique using electronic expansion valve controlled by VFD (variable frequency drive), which can automatically adjusts the operating parameters, ensure wonderful working performance and lower energy consumption.
- 2. Automatically vaporizes defrost water, drainage is not required.
- 3. Patented top-mounted removable independently cooling system,whole unit can be replaced with new one immediately.
Interchangeable different temperature ranges cassette unit allows flexible application, also easy to maintain.
- 4. Removable door gasket, easy to replace the heaters inside.
- 5. Adjustable legs or castors upon request.

1. 专利准变频电子膨胀阀制冷系统，配备自主研发的控制技术，自动调节制冷系统运行参数,节能高达30%，克服毛细管工况适应性差且制冷过程不能精确控制的缺点，且具备多重保护功能; 2. 自动蒸发化霜水，不需要排水管; 3. 具有专利技术的嵌入可移动式整体制冷系统，包含风冷蒸发器系统，很方便更换整套全新的制冷系统，不同温度范围的制冷系统可互换，灵活应用，易于维护; 4. 门框加热丝可更换; 5. 调节脚和脚轮可选

Specifications

- 1. Accommodates 2/1 GN size
- 2. Foodsafe 304 grade stainless steel exterior and interior
- 3. Galvanised steel exterior back and base
- 4. Fitted with cylindrical lock for doors
- 5. 1.2 mm thick durable 304 grade stainless steel table top
- 6. Accommodates 400*600mm GN size for Bakery

- 1. 可置2/1分数盘
- 2. 内外食品级304不锈钢
- 3. 背板和底部镀锌板
- 4. 每个门配圆形锁
- 5. 1.2mm厚的304不锈钢台面
- 6. 可置400*600mm的GN盘和烤盘

Options

- 1. 304 grade stainless steel exterior and interior back/ base
- 2. Heated film glass door
- 3. Pass through door
- 4. Saladette opening
- 5. Wooden board under table top
- 6. Table top extension
- 7. 2mm thick 304 grade stainless steel table top
- 8. 2, 3 or 1/3 +2/3 drawers bank
- 9. Cylindrical lock for drawers
- 10. Internal light for door type
- 11. Lock plate
- 12. Right-hand-side condenser unit
- 13. Remoted type condensing unit
- 14. Back/ side splash
- 15. Front/ side skirting
- 16. Castors in Lieu of legs
- 17. 50Hmm skirting with louvre for sitting on plinth
- 18. Additional shelving/ trayslides for door type
- 19. 220V/60HZ/1PH,110V/60Hz

- 1. 内、外、背板和底部全304不锈钢
- 2. 镀膜玻璃门
- 3. 双通门
- 4. 平台上装沙拉盘
- 5. 工作台下加木板
- 6. 工作台面加宽
- 7. 台面不锈钢厚度为2mm
- 8. 2个, 3个, 1/3 +2/3抽屉可选
- 9. 抽屉带锁

- 10. 开门型里面装灯
- 11. 锁板
- 12. 右侧制冷机组
- 13. 分体式机组（外置机组）
- 14. 侧面或背部加防溅板
- 15. 前/侧裙脚
- 16. 可选脚轮代替调节脚
- 17. 50mm高的前面底部裙脚
- 18. 开门型产品额外加配层架或支条
- 19. 电源电压可选

Counter Chiller & Freezer

平台冷柜



Product Code

W2UXDD
S2UXDD

1 Temperature Range 温度范围
H = +1℃/+4℃
M = -2℃/+2℃
L = -18℃/-22℃
2 Material of the stainless steel 不锈钢材质
PW : Classic Collection, #304 s/s exterior(0.5) and interior(0.5), PW: 经典系列, 内外#304不锈钢
RW : Professional Collection, #201 s/s exterior(0.5) and interior(0.5) RW: 专业系列, 内外#201不锈钢
3 Depth of chiller & freezer 深度
S : 660 mm
W : 760 mm

4 Collections 系列
W : Upright Chiller& Freezer W系列平台柜
S : Counter Chiller & Freezer S系列平台柜
5 Number of compartment 门洞数量
1 : 1 compartment 1个门洞
2 : 2 compartment 2个门洞
6 Configuration 配置
H : Half solid door 发泡半门
F : Full solid door 发泡全门
D : Half glass door 玻璃半门
G : Full glass door 玻璃全门
N : Two drawers bank 双抽屉

Counter Chiller & Freezer

平台冷柜

Product List



Counter Chiller & Freezer

平台冷柜

Technical Data

Model 型号	HW1UXD	HW1UXN	HW1UXW	HW1UXD	HW1UXWW	HW1UXD
Temp Range 温度范围	+1℃/+4℃			-2℃/+2℃	-2℃/+2℃	-18℃/-22℃
External Dimension (mm) 外形尺寸						
Width 长	1152					
Depth 宽	760					
Height 高	850					
Internal Dimension (mm) 内部尺寸						
Width 长	587					
Depth 宽	658					
Height 高	558					
Thickness of 304 grade stainless steel (mm) #304不锈钢厚度						
Exterior 外部	0.5					
Interior 内部	0.5					
Door or drawer 门/抽屉	0.7					
Open Depth (mm) 开门深度						
Door type 开门型	1380					
Drawer type 抽屉型	1466					
Maximum loading height of drawer (mm per drawer) 抽屉最高装载高度						
2 drawers bank 双抽屉	150					
3 drawers bank 三抽屉	100					
Capacity (cu.ft / liters) 容积	195 L					
Power supply 电源	220V/50HZ(220V/60HZ, 110V/60HZ)					
Power Input - Running (amps) 电流	2.4A					3.5A
Rating Power (watts) 输入功率	415W					449W
Compressor (HP) 压缩机	1/4					3/8
Refrigerant制冷剂						
Type 类型	R134a					R404a
Weight (g) 灌注量	280g					350g
Standard fitting for door type 门式标准配件						
PE coated shelves 浸塑网架	1					
Trayslides (pair) 网架托角	1					
Packing 包装	Simple package					
Packing Size 包装尺寸	1175*780*885mm					
Shipping 装柜数量						
Qty/20'GP	22					
Qty/40'GP	46					
Qty/40'HQ	46					

Optional Refrigerant : R290

Counter Chiller & Freezer

平台冷柜

Technical Data



Model 型号	H-W2UXDD	H-W2UXNN	H-W2UXDDG	M-W2UXDD	L-W2UXDD
Temp Range 温度范围	+1℃/+4℃			-2℃/+2℃	-18℃/-22℃
External Dimension (mm) 外形尺寸					
Width 长	1815				
Depth 宽	760				
Height 高	850				
Internal Dimension (mm) 内部尺寸					
Width 长	1249				
Depth 宽	658				
Height 高	558				
Thickness of 304 grade stainless steel (mm) #304不锈钢厚度					
Exterior 外部	0.5				
Interior 内部	0.5				
Door or drawer 门/抽屉	0.7				
Open Depth (mm) 开门深度					
Door type 开门型	1380				
Drawer type 抽屉型	1466				
Maximum loading height of drawer (mm per drawer)抽屉最高装载高度					
2 drawers bank 双抽屉	150				
3 drawers bank 三抽屉	100				
Capacity (cu.ft / liters) 容积	416L				
Power supply 电源	220V/50HZ(220V/60HZ, 110V/60HZ)				
Power Input - Running (amps) 电流	2.5A				4.3A
Rating Power (watts) 功率	430W				660W
Compressor (HP) 压缩机	1/4				1/2
Refrigerant 制冷剂					
Type 类型	R134a				R404a
Weight (g) 灌注量	280g				350g
Standard fitting for door type 门式标准配件					
PE coated shelves 浸塑网架	2				
Trayslides (pair) 网架托角	2				
Packing 包装	Simple package				
Packing Size 包装尺寸	1835*780*885mm				
Shipping 装柜数量					
Qty/20'GP	14				
Qty/40'GP	28				
Qty/40'HQ	28				

Optional Refrigerant : R290

Counter Chiller & Freezer

平台冷柜

Technical Data



Model 型号	H-W3UXDDD	H-W3UXDNN	H-W3UXWWW	HW3UXDDD	HW3UXDDD
Temp Range 温度范围	+1℃/+4℃			-2℃/+2℃	-18℃/-22℃
External Dimension (mm) 外形尺寸					
Width 长	2476				
Depth 宽	760				
Height 高	850				
Internal Dimension (mm) 内部尺寸					
Width 长	1911				
Depth 宽	658				
Height 高	558				
Thickness of 304 grade stainless steel (mm) #304 不锈钢厚度					
Exterior 外部	0.5				
Interior 内部	0.5				
Door or drawer 门/抽屉	0.7				
Open Depth (mm) 开门深度					
Door type 开门型	1380				
Drawer type 抽屉型	1466				
Maximum loading height of drawer (mm per drawer) 抽屉最高装载高度					
2 drawers bank 双抽屉	150				
3 drawers bank 三抽屉	100				
Capacity (cu.ft / liters) 容积					
637L					
Power supply 电源					
220V/50HZ(220V/60HZ, 110V/60HZ)					
Power Input - Running (amps) 电流	2.9A			4.3A	
Rating Power (watts) 功率	510W			660W	
Compressor (HP) 压缩机	3/8			3/4	
Refrigerant制冷剂					
Type 类型	R134a				R404a
Weight (g) 灌注量	300g				410g
Standard fitting for door type 门式标准配件					
PE coated shelves 浸塑网架	3				
Trayslides (pair) 网架托角	3				
Packing 包装	Simple package				
Packing Size 包装尺寸	2495*780*885mm				
Shipping 装柜数量					
Qty/20'GP	8				
Qty/40'GP	16				
Qty/40'HQ	16				

Optional Refrigerant : R290

Counter Chiller & Freezer

平台冷柜

Technical Data



Model 型号	H-S1UXD	H-S1UXW	H-S1UXN	M-S1UXD	L-S1UXD
Temp Range 温度范围	+1℃/+4℃			-2℃/+2℃	-18℃/-22℃
External Dimension (mm) 外形尺寸					
Width 长				955	
Depth 宽				660	
Height 高				850	
Internal Dimension (mm) 内部尺寸					
Width 长				390	
Depth 宽				563	
Height 高				558	
Thickness of 304 grade stainless steel (mm) #304不锈钢厚度					
Exterior 外部				0.5	
Interior 内部				0.5	
Door or drawer 门/抽屉				0.7	
Open Depth (mm) 开门深度					
Door type 开门型				1083	
Drawer type 抽屉型				1266	
Maximum loading height of drawer (mm per drawer) 抽屉最高装载高度					
2 drawers bank 双抽屉				150	
3 drawers bank 三抽屉				100	
Capacity (cu.ft / liters) 容积				123L	
Power supply 电源	220V/50HZ(220V/60HZ, 110V/60HZ)				
Power Input - Running (amps)	2.9A				3.5
Rating Power (watts) 功率	440W				449
Compressor (HP) 压缩机	1/4				
Refrigerant制冷剂					
Type 类型	R134a				R404a
Weight (g) 灌注量	270g				390
Standard fitting for door type 门式标准配件					
PE coated shelves 浸塑网架				1	
Trayslides (pair) 网架托角				1	
Packing 包装	Simple package				
Packing size 包装尺寸	975*680*885mm				
Shipping 装柜数量					
Qty/20'GP				34	
Qty/40'GP				70	
Qty/40'HQ				70	

Optional Refrigerant : R290

Counter Chiller & Freezer

平台冷柜

Technical Data



Model 型号	HS2UXDD	H-S2UXNN	H-S2UXWW	M-S2UXDD	L-S2UXDD
Temp Range 温度范围	+1℃/+4℃			-2℃/+2℃	-18℃/-22℃
External Dimension (mm) 外形尺寸				1420	
Width 长	660				
Depth 宽	850				
Height 高					
Internal Dimension (mm) 内部尺寸					
Width 长	855				
Depth 宽	563				
Height 高	558				
Thickness of 304 grade stainless steel (mm) #304不锈钢厚度					
Exterior 外部	0.5				
Interior 内部	0.5				
Door or drawer 门/抽屉	0.7				
Open Depth (mm) 开门深度				1083	
Door type 开门型	1266				
Drawer type 抽屉型					
Maximum loading height of drawer (mm per drawer) 抽屉最高装载高度					
2 drawers bank 双抽屉	150				
3 drawers bank 三抽屉	100				
Capacity (cu.ft / liters) 容积				267L	
Power supply 电源				220V/50HZ(220V/60HZ, 110V/60HZ)	
Power Input - Running (amps)				3A	4.6A
Rating Power (watts) 功率				460W	770W
Compressor (HP) 压缩机				1/4	
Refrigerant 制冷剂					
Type 类型	R134a				R404a
Weight (g) 重量	270g				350g
Standard fitting for door type 门式标准配件					
PE coated shelves 浸塑网架	2				
Trayslides (pair) 网架托角	2				
Packing 包装				Simple package	
Packing size 包装尺寸				1440*680*885mm	
Shipping 装柜数量					
Qty/20'GP	22				
Qty/40'GP	48				
Qty/40'HQ	48				

Optional Refrigerant : R290

Counter Chiller & Freezer

平台冷柜

Technical Data



Model 型号	H-S3UXDDD	H-S3UXNNN	H-S3UXWWW	M-S3UXDDD	L-S3UXDDD
Temp Range 温度范围	+1℃/+4℃			-2℃/+2℃	-18℃/-22℃
External Dimension (mm) 外形尺寸					
Width 长	1885				
Depth 宽	660				
Height 高	850				
Internal Dimension (mm) 内部尺寸					
Width 长	1737				
Depth 宽	563				
Height 高	558				
Thickness of 304 grade stainless steel (mm) #304 不锈钢厚度					
Exterior 外部	0.5				
Interior 内部	0.5				
Door or drawer 门/抽屉	0.7				
Open Depth (mm) 开门深度					
Door type 开门型	1083				
Drawer type 抽屉型	1266				
Maximum loading height of drawer (mm per drawer) 抽屉最高装载高度					
2 drawers bank 双抽屉	150				
3 drawers bank 三抽屉	100				
Capacity (cu.ft / liters) 容积	590L				
Power supply 电源	220V/50HZ(220V/60HZ, 110V/60HZ)				
Power Input - Running (amps)	3A			4.8	
Rating Power (watts) 功率	480W			730	
Compressor (HP) 压缩机	1/4			1/1	
Refrigerant制冷剂					
Type 类型	R134a			R404a	
Weight (g) 灌注量	270g			420	
Standard fitting for door type 门式标准配件					
PE coated shelves 浸塑网架	3				
Trayslides (pair) 网架托角	3				
Packing 包装	Simple package				
Packing size 包装尺寸	1905*680*885mm				
Shipping 装柜数量					
Qty/20'GP	18				
Qty/40'GP	36				
Qty/40'HQ	36				

Optional Refrigerant : R290

Counter Chiller & Freezer

平台冷柜

Technical Data



Model 型号	H-S4UXDDDD	H-S4UXNNWW	M-S4UXDDDD	L-S4UXDDDD
Temp Range 温度范围	+1℃/+4℃		-2℃/+2℃	-18℃/-22℃
External Dimension (mm) 外形尺寸				
Width 长	2350			
Depth 宽	660			
Height 高	850			
Internal Dimension (mm) 内部尺寸				
Width 长	1785			
Depth 宽	563			
Height 高	558			
Thickness of 304 grade stainless steel (mm) #304 不锈钢厚度				
Exterior 外部	0.5			
Interior 内部	0.5			
Door or drawer 门/抽屉	0.7			
Open Depth (mm) 开门深度				
Door type 开门型	1083			
Drawer type 抽屉型	1266			
Maximum loading height of drawer (mm per drawer) 抽屉最高装载高度				
2 drawers bank 双抽屉	150			
3 drawers bank 三抽屉	100			
Capacity (cu.ft / liters) 容积	590L			
Power supply 电源	220V/50HZ(220V/60HZ, 110V/60HZ)			
Power Input - Running (amps)	3A		5.4	
Rating Power (watts) 功率	490W		920	
Compressor (HP) 压缩机	3/8		3/4	
Refrigerant制冷剂				
Type 类型	R134a		R404a	
Weight (g) 灌注量	270g		410g	
Standard fitting for door type 门式标准配件				
PE coated shelves 浸塑网架	4			
Trayslides (pair) 网架托角	4			
Packing 包装	Simple package			
Packing size 包装尺寸	2370*680*885mm			
Shipping 装柜数量				
Qty/20'GP	12			
Qty/40'GP	24			
Qty/40'HQ	24			

Optional Refrigerant : R290