

Upright Chiller & Freezer

高身冷柜

Key Features

1. Patented semi frequency variable technique using electronic expansion valve controlled by VFD (variable frequency drive), which can automatically adjust the operating parameters, ensure wonderful working performance and lower energy consumption.
 专利准变频电子膨胀阀制冷系统，配备自主研发的控制技术，自动调节制冷系统运行参数，节能高达30%，克服毛细管工况适应性差且制冷过程不能精确控制的缺点，且具备多重保护功能
2. Automatically vaporizes defrost water, drainage is not required. 自动蒸发化霜水，不需要排水管
3. Patented top-mounted removable independently cooling system, whole unit can be replaced with new one immediately.
 Interchangeable different temperature ranges cassette unit allows flexible application, also easy to maintain.
 具有专利技术的嵌入可移动式整体制冷系统，包含风冷蒸发器系统，很方便更换整套全新的制冷系统，不同温度范围的制冷系统可互换，灵活应用，易于维护
4. Removable door gasket, easy to replace the heaters inside. 门框加热丝可更换
5. Adjustable legs or castors upon request.
 调节脚和脚轮可选



Specifications

1. Accommodates 2/1 GN size
2. Foodsafe 304 grade stainless steel exterior and interior
3. Galvanised steel exterior back and base
4. Fitted with cylindrical lock for doors

1. 可置2/1分数盘
2. 内外食品级304不锈钢
3. 背板和底部镀锌板
4. 每个门配圆形锁

Options

1. 304 grade stainless steel exterior and interior back/ base
2. Heated film glass door
3. Pass through door
4. 2 or 3 drawers bank for low half section
5. Cylindrical lock for drawers
6. Internal light for door type
7. Castors in Lieu of legs
8. Additional shelving / trayslides
9. 220V/60HZ/1PH, 110V/60Hz

1. 内、外、背板和底部全304不锈钢
2. 双通门系列
3. 每一个下部的半门可换成2/3个抽屉
4. 抽屉配圆锁
5. 发泡/玻璃门系列柜体内部可安装LED灯
6. 调节脚可换成脚轮
7. 额外增加层架/托条
8. 电源电压可选

Upright Chiller & Freezer

高身冷柜

Product Code

J2T

1 Temperature Range 温度范围

H = +1/+4 C

M = -2/+2 C

L = -18/-22 C

2 Material of the stainless steel 不锈钢材质

PW : Classic Collection, #304 s/s exterior(0.5) and interior(0.5), PW: 经典系列, 内外#304不锈钢

RW : Professional Collection, #201 s/s exterior(0.5) and interior(0.5) RW: 专业系列, 内外#201不锈钢

3 Depth of chiller & freezer 深度

815 mm

4 Collections 系列

J : Upright Chiller& Freezer J: 高身柜系列

5 Number of compartment 门洞数量

1 : 1 compartment 1个门洞

2 : 2 compartment 2个门洞

6 Configuration 配置

H : Half solid door 发泡半门

F : Full solid door 发泡全门

D : Half glass door 玻璃半门

G : Full glass door 玻璃全门

N : Two drawers bank 双抽屉



Upright Chiller & Freezer

高身冷柜

Product List



Upright Chiller & Freezer

单门高身冷柜

Technical Data



Model 型号	H-J1T	M-J1T	L-J1T			
Temp Range 温度范围	+1°C/+4°C	-2°C/+2°C	-18°C/-22°C			
External Dimension (mm) 外形尺寸						
Width 长	737					
Depth 宽	815					
Height 高	1980					
Internal Dimension (mm) 内部尺寸						
Width 长	587					
Depth 宽	683					
Height 高	1370					
Thickness of 304 grade stainless steel (mm) #304 不锈钢厚度						
Exterior 外部	0.5					
Interior 内部	0.5					
Door or drawer 门/抽屉	0.7					
Open Depth (mm) 开门深度						
Door type 开门型	1435					
Drawer type 抽屉型	1525					
Maximum loading height of drawer (mm per drawer) 抽屉最高装载高度						
2 drawers bank 双抽屉	100					
3 drawers bank 三抽屉	150					
Capacity (cu.ft / liters) 容积	550L					
Power supply 电源 220V/50HZ(220V/60HZ, 115V/60HZ)						
Power Input - Running (amps) 电流	3.0A	3.2A	4.3A	4.4A		
Rating Power (watts) 功率	480W	530W	690W	760W		
Compressor (HP) 压缩机	1/4		3/4			
Refrigerant 制冷剂						
Type 类型	R134a		R404a			
Weight 灌注量	310g		370g			
Standard fitting for door type 门式标准配件						
PE coated shelves 浸塑网架	3	2	3	3	2	3
Trayslides (pair) 网架托角	3	2	3	3	2	3
Packing 包装	Simple package					
Packing Size 包装尺寸	777*855*2030mm					
Shipping 装柜数量						
Qty/20'GP	14					
Qty/40'GP	28					
Qty/40'HQ	28					

Optional Refrigerant : R290

Upright Chiller & Freezer

高身冷柜

Technical Data



Model型号	H-J2TSS	H-J2TSS-GD	M-J2TSS	M-J2TSS
Temp Range温度范围	+1°C/+4°C		-2°C/+2°C	-18°C/-22°C
External Dimension (mm) 外形尺寸				
Width 长	1400			
Depth 宽	815			
Height 高	1980			
Internal Dimension (mm) 内部尺寸				
Width 长	1250			
Depth 宽	683			
Height 高	1384			
Thickness of 304 grade stainless steel (mm) #304 不锈钢厚度				
Exterior 外部	0.5			
Interior 内部	0.5			
Door or drawer 门/抽屉	0.7			
Open Depth (mm) 开门深度				
Door type 开门型	1435			
Drawer type 抽屉型	1525			
Maximum loading height of drawer (mm per drawer) 抽屉最高装载高度				
2 drawers bank 双抽屉	150			
3 drawers bank 三抽屉	100			
Capacity (cu.ft / liters) 容积	1170L			
Power supply 电源	220V/50HZ(220V/60HZ, 115V/60HZ)			
Power Input - Running (amps)	3.1A		5.5A	
Rating Power (watts) 功率	520W		950W	
Compressor (HP) 压缩机	3/8		1	
Refrigerant 制冷剂				
Type 类型	R134a		R404a	
Weight 灌注量	400g		750g	
Standard fitting for door type 门式标准配件				
PE coated shelves 浸塑网架	6	4	6	4
Trayslides (pair) 网架托角	6	4	6	4
Packing 包装	Simple package			
Packing Size 包装尺寸	1440*855*2030mm			
Shipping 装柜数量				
Qty/20'GP	8			
Qty/40'GP	16			
Qty/40'HQ	16			

Optional Refrigerant : R290

Upright Chiller & Freezer

高身冷柜

Technical Data



Model型号	H-J2TSSGD	H-J2TSSGD	L-J2T-KA
Temp Range温度范围	+1°C/+4°C		-18°C/-22°C
External Dimension (mm) 外形尺寸			
Width 长	1400		
Depth 宽	815		
Height 高	1980		
Internal Dimension (mm) 内部尺寸			
Width 长	1250		
Depth 宽	683		
Height 高	1384		
Thickness of 304 grade stainless steel (mm) #304 不锈钢厚度			
Exterior 外部	0.5		
Interior 内部	0.5		
Door or drawer 门/抽屉	0.7		
Open Depth (mm) 开门深度			
Door type 开门型	1435		
Drawer type 抽屉型	1525		
Maximum loading height of drawer (mm per drawer) 抽屉最高装载高度			
2 drawers bank 双抽屉	150		
3 drawers bank 三抽屉	100		
Capacity (cu.ft / liters) 容积	1170L		
Power supply 电源	220V/50HZ(220V/60HZ, 115V/60HZ)		
Power Input - Running (amps)	3.5A		5.7A
Rating Power (watts) 功率	590W		1000W
Compressor (HP) 压缩机	3/8		1
Refrigerant 制冷剂			
Type 类型	R134a		R404a
Weight 灌注量	400g		750g
Standard fitting for door type 门式标准配件			
PE coated shelves 浸塑网架	6		
Trayslides (pair) 网架托角	6		
Packing 包装	Simple package		
Packing Size 包装尺寸	1440*855*2030mm		
Shipping 装柜数量			
Qty/20'GP	8		
Qty/40'GP	16		
Qty/40'HQ	16		

Optional Refrigerant : R290